

Advice on Width, area and height on routes used by equestrians

The law and management of public access rights vary widely between the four countries of the United Kingdom. Practical elements of the following advice apply in all countries but the legal requirements in Scotland and Northern Ireland may differ from those in England and Wales.

More advice is available on www.bhs.org.uk/accessadvice.

IMPORTANT This guidance is general and does not aim to cover every variation in circumstances. Where it is being relied upon, The Society recommends seeking advice specific to the site.

In providing specifications for equestrian ways and facilities, the British Horse Society considers all equestrian users, which may result in a specification which might not be appropriate in all circumstances. The recommendations should be read with this in mind. If the specification seems inappropriate in a situation, the Society strongly advises that it is consulted to establish what may be acceptable at a particular site.

Equestrians, that is, riders and horse-drawn vehicle drivers, like walkers and cyclists, come in all sizes, with considerable variety in their interests, skills, needs and preferences and this should be considered in providing or improving ways used by equestrians.

Contents

Width	1
Width for new routes	2
Area	4
Height	5

Width

There is no default width for a bridleway or byway. Some rights of way have a width shown in their Statement,¹ but it is not necessarily accurate as they commonly describe a beaten earth path rather than the width used, or fail to recognise the space used when people pass one another. This leads to a difficult situation where an unenclosed bridleway or byway has an unreasonably narrow width shown in the Statement, for example six feet,² and becomes fenced as a six feet (1.8m) wide corridor,

¹ The Definitive Map and Statement is conclusive evidence of the rights and details shown on it but without prejudice to any rights not yet shown. Widths are commonly not recorded or are inaccurate.

² Most unreasonable widths are those recorded in the 1950s, in feet, when there was inadequate briefing of what to record and awareness of historical evidence of width. Widths arising from more recent legal orders are likely to be more accurate.

resulting in a useable width of only a metre because users naturally avoid passing close to a fence, wall or hedge which could snag them.

It is clear from observing users pass one another on unenclosed land that while pedestrians may pass each other comfortably within a 2 metre width, two riders, or any combination of riders, cyclists, carriage-drivers and pedestrians (especially with dogs) will not pass so close to one another by choice and are more likely to allow at least a metre between them, therefore using around 3 metres or more, when without fences on one or both sides.

Width for new routes

The intention of the widths recommended here is to provide a *useable* width of minimum 3 metres for a bridleway or 4 metres for a byway, at all seasons.

If the way is alongside or between hedges, fences, walls or other boundary, a useable width is likely to require an additional half a metre alongside the boundary, giving an overall width of 4 metres (bridleway) or 5 metres (byway) between fences or hedges. This is because any user will avoid the ground immediately adjacent to the boundary, particularly adjacent to barbed wire or thorny plants or where ground vegetation will build up and could hide debris, trip hazards or dog mess.

Alongside or between hedges will require a width sufficient for keeping the hedges cut. More than half a metre may be required where hedge growth must be accommodated for fast-growing hedge species or where the hedge is not cut each year.

On a byway where the surface may become rutted, a driver of a horse-drawn vehicle may need to avoid ruts created by motor vehicles as they could be too deep or widely spaced so a greater width could be required.

The Society recognises that the circumstances for all new bridleways and byways (including diversions) vary and on occasion, particularly to gain a route away from motor vehicles, a width less than the recommended standard may be better than using a motor vehicular road. A lesser width may be acceptable where users are prepared to stop for each other to pass. For situations where a lesser width is considered because the recommendation is not possible, advice and agreement should be sought from the BHS.

In Diversion Orders

The Society encourages Order Making Authorities to adopt a recommended standard width of 5 metres for diverted bridleways and byways.

The Society will usually object to bridleway or byway diversion proposals where the width of the replacement way is less than 4 metres unless exceptional circumstances apply.

In Creation Agreements and Orders

The Society encourages Order Making Authorities to adopt a recommended standard of 5 metres m width for new bridleways and restricted byways whenever possible but recognises that a lesser width may be necessary in order to create any way in some cases.

For greenways and those considered to be of strategic importance, more than 5 metres allows comfortable space for different types of user, particularly if used by cyclists at speed. If segregation is thought necessary in a particular circumstance then the greater width makes this possible. Where available, a width greater than 5 metres also allows for the provision of trees and hedges and benches for resting to increase the attraction and health benefits of the route for all users.

For general maintenance or enforcement purposes

Where there is no substantive evidence of a right of way's width, the Society will request that a width of no less than 3 metres is cleared. If the Definitive Statement includes a width, then a minimum of that width should be reinstated so long as it is wide enough to be practical (minimum 3 metres if bounded on one or both sides, 2 metres if open, based on the provisions of the Rights of Way Act 1990 for arable fields).

The Highways Act 1980 Section 164 provides that the presence of barbed wire by a right of way can constitute a public nuisance. Users of the way should be protected from the barbs by a flat rail on the side of the right of way. A greater width may be required to provide sufficient passing space clear of the barbed wire. Electrified fencing should be treated as for barbed wire and avoided along or across bridleways and byways.

The width between gateposts (Highways Act 1980 Section 145) should be 1.5 metres on a bridleway, 3 metres on all byways and roads.

Where bollards are considered to restrict vehicular access, the minimum width should be 1.5 metres on a bridleway, 1.8 metres on a byway (see BHS Advice on Vehicle Barriers)..

In Modification Orders

The Society will object if the width stated is less than that for which there is substantive evidence, or if a single whole route width is stated where there is evidence that the right of way is wider in places.

If evidence relies on an inclosure awarded width of more than sixteen feet, the Society may, depending on local circumstances, be open to subsequent extinguishment of width in excess of 5 metres provided that the remaining width is of a surface and nature which is resilient to use.

Area

Where it is necessary to turn a ridden horse (in order to close a gate, for example), the area of manoeuvring space should ideally be no less than 4 metres by 4 metres; large horses may require that area to turn easily. The absolute minimum space required is a diameter of 3 metres on clear, flat ground with no protrusions or overhanging vegetation. A greater area is preferred to avoid potential of injury on fencing, gates or other structures and if ground is uneven or there is overhanging vegetation.

The more that area is restricted, the more important it is that the surface is firm, level and even and kept clear of overgrowth.

Horse-drawn vehicles are likely to need to turn only if there is an obstruction which prevents them continuing, which could present a problem if an area less than 5 metres (depending on size of turnout) is available although, if absolutely necessary, a horse can be unhitched and the vehicle turned separately, but this is not a task to be considered normal or 'convenient' for a highway user.

Space and Safety at Gates for Ridden Horses

See BHS Advice on Gates. The recommended area for manoeuvring a ridden horse at a gate is 4 metres by 4 metres, incorporating 1.2 metres in line with the gate beyond the clapper post.

Manoeuvring a horse through a gate is particularly hazardous for riders and any obstacle or impediment within or close to the manoeuvring space and gateway greatly increases the difficulty of operating the gate safely. The manoeuvring space must be on firm, level and even ground without trip hazards or overgrowth.

Electric fencing near gates can present a particularly serious hazard if it is possible for the horse, rider or gate to contact the electrified wire. Please see BHS Advice on Electric Fencing.

Drivers of horse-drawn vehicles are likely to be accompanied by another person who will open and close a gate. Additional space is not required except at a roadside where a gate should be set back by at least 5 metres to avoid putting horse and vehicle at risk from road traffic while waiting for the groom to open or close the gate.

Fenced enclosures for waiting areas or separation pens

There is sometimes a need for enclosed areas, perhaps at road crossings, or at the end of a bridge where stock security is required but a gate should never be installed on the end of the bridge which is less than 3 metres wide. For any enclosed area it is recommended that:

- Clear manoeuvring space of at least 4 metres by 4 metres is required within the pen.
- All fencing should be post and rail wooden fencing, no wire, wire netting or barbed wire. If barbed wire is required for stock control, it should be shielded on the bridleway side by a plain rail.

- The ground throughout the structure should be firm, level and free from deep mud or vegetation that would reduce the useable area.

All other recommendations for gates, catches and surroundings apply (free of protrusions, barbed wire and so on, see BHS Advice on Gates).

If an area is likely to need to accommodate more than one ridden horse, such as a waiting area to cross a road, then more than 4 metres length or width will be required. For driven horses, a minimum of 6 metres length will be required.

Fencing

As a general guide the following types of fencing are suitable for horses and can be used safely alongside rights of way, in order of preference:

1. Post and rail wooden fencing
2. Posts with impact resistant plastic rails
3. Posts with flexi-rails (PVC or rubber-coated webbing)
4. Vertical close board fencing has been used at roadside locations in waiting pens for light controlled crossings but while it may help horses feel safer while waiting, it will limit sightlines for equestrians

Wire fencing (both straight and barbed) is less desirable and potentially injurious. This is more likely if it is not well installed and maintained with firm upright posts and fully tensioned wire. If barbed wire is proved to be a nuisance it is illegal (Section 164 Highways Act 1980).

Metal palisade security fencing with spikes on top, commonly seen by railways, should be avoided alongside bridleways and byways as the injuries that could be incurred by a rider falling onto the fence if thrown from a horse could easily be fatal.

Electric fencing should never be used alongside or across bridleways or byways except where proper provision has been made at gates and the way is wide enough between the fencing (see BHS Advice on Electric Fencing).

Standard stock fencing is generally between 1,100 and 1,200mm high.

Height

Overgrowth

The average height of a mounted rider is 2.75 metres above ground level, tall riders on large horses could be over 3 metres. Overhanging branches, overgrowth from the sides and any other obstructions should be cleared to a height of 3.4 metres on all routes.

Horse-drawn vehicles vary in height but clearance to accommodate riders will also give clearance for drivers as those vehicles higher than a rider are very unlikely to be used as exercise vehicles.

Underpasses and Tunnels

Where underpasses are constructed to enable equestrians to cross below a road or railway, the ideal height is greater than 3.4 metres, and a width of 5 metres. Generally, the longer the underpass, the more desirable it will be to meet the ideal height or width, however, all situations should be judged individually as there are many factors to take into account.

While the Society seeks the desirable height and width for underpasses, in exceptional circumstances a lower height or width may be tolerated for a crossing of a road or railway which would be unsafe to cross at grade and where there is no option to increase the height, such as where the water table is high.

When a lower height for an underpass is locally agreed as acceptable, equestrians would be expected to dismount although those with smaller horses and low horse-drawn vehicles may choose not to if they are comfortable with the clearance. It should be left to the rider's discretion as they are unlikely to risk themselves or their horse and are the best to judge what is appropriate for them. When a lower height has been locally accepted as unavoidable, a mounting block should be provided at either end (see BHS Advice on Mounting Blocks) for those who are forced to dismount.

Where a compromise has been reached that a low or narrow underpass is the best solution available, equestrians must not be prevented from using it as many will be capable of doing so once the horse has accepted the environment.

There are many examples through the country of equestrian using disused railway tunnels and long underpasses, such as under motorways; there is no reason to exclude horses from them. Examples include several on the Monsal Trail in Derbyshire and the Denstone Trail in Staffordshire, both disused railway lines, and the Trans Pennine Trail at Thurgoland. Some tunnels/underpasses are quite narrow but it is not an issue so long as all users know to expect others and to pass with care and consideration. Signs are important on shared use trails to make clear to all users to expect horses.

Lighting in underpasses or tunnels depends very much on the site. Horses can generally see better in the dark than humans, but have greater difficulty with sudden changes in light, such as moving from bright light into an underpass, their eyes adjust more slowly, which may cause a horse to be reluctant to move forward, however, the light level needed to mitigate is not great and certainly no more than would be normal for a pedestrian route.

British Standard BS 5489-1:2020 section 7.4.7. gives requirements for lighting 'subways'. BS 4589-1 suggests that daytime lighting should be double that required during darkness hours, however, where an underpass is part of a rural route that is unlit, this is likely to be excessive.

Standards do not refer to requirements for horses but it may be assumed that provision for pedestrians is likely to be acceptable.

Please see www.bhs.org.uk/accessadvice for all BHS Advice referred to above.